



TECHNICAL DATA SHEET
LTP GRIMEX
multi-purpose intensive cleaner

Effective for removing oil, grease, ingrained dirt, grime and old wax layers. Suitable for use on terracotta, quarry tiles, slate, marble, stone and ceramic wall tiles. May be used in dilute or concentrated form.

Important: Test the solution on an inconspicuous area before general application. Any alkalinity remaining on surfaces treated with this product should be completely neutralised. This may be done with a little clean water applied by sponge.

Directions for use:

In mild cases and on absorbent tiles: Dilute 1 part Grimex in 10 parts warm water. Apply with a cloth or mop. Wipe off thoroughly with a clean damp cloth.

In more severe cases: Dilute 1 part Grimex in 3 parts warm water. Apply liberally, spreading over surface of tiles. If necessary agitate with a scrubbing brush. leave to react for 5-10 minutes, keeping wet with additional Grimex solution. Mop up and rinse thoroughly with clean water.

In extremely severe cases: Use undiluted and agitate with scrubbing brush if necessary. Neutralise treated surface with clean water after use.

Coverage:

In mild cases -approximately 50m²

In more severe cases -approximately 20m²

In extremely severe cases -approximately 5-10m²

Attention: Keep out of reach of children Use gloves to apply Avoid contact with eyes and skin In case of contact with eyes rinse with plenty of water and seek medical advice In case of swallowing seek medical advice This product should not be used for every day cleaning of floors sealed with LTP Ironwax or Beeswax polishes

For any technical questions, please ring technical helpline: 01823 666 213.

Click to see all [stone maintenance products](#)