



**TECHNICAL DATA SHEET  
LTP IRONWAX SATIN**

*low maintenance satin finish self-shine sealer for unglazed quarry tiles, slate, stone and unpolished marble.*

Easy to apply, self-shine satin finish acrylic sealer. Enhances the colour and texture of floors. Protects against stains and stubborn dirt. Easy to maintain. May be used on quarry tiles, terracotta, slate, stone, terrazzo and unpolished marble.

**Directions for use:**

Ensure surface to be treated is completely clean, dry and free from cement and grout stain (see LTP Grout Stain Remover). Any moisture in the floor may cause the LTP Ironwax Satin to dry opaque or prevent the seal from reaching full hardness. Using a paintbrush or soft fluff-free cloth, apply a thin coat of LTP Ironwax Satin evenly in one direction. Do not rub or buff the surface but allow to dry (approx 1 hour). Apply a second coat at right angles to the first. Subsequent coats should be applied at right angles to the previous. Do not over apply as too many coats may cause unsightly build up of LTP Ironwax Satin and/or reduce the efficiency of the product. LTP Ironwax Satin hardens after about an hour but will take a further three days to achieve full hardness and become fully water resistant. If in doubt, experiment on spare tiles to establish the optimum number of coats before general use.

**Coverage:**

Approximately 15-40mper litre (one coat) depending on substrate porosity.

**Attention:** Avoid shaking the bottle prior to use. Frothing of liquid may lead to an inconsistent finish. Keep out of reach of children. Store in a frost proof place. Avoid using strong detergents and kitchen to wash floors treated with LTP Ironwax Satin. Do not use below freezing. After contact with skin, wash with soap and water. Ironwax Satin may not properly adhere to the most highly vitrified quarry tiles or ceramics. If in doubt, test on an inconspicuous area prior to general application. On higher porosity floor materials LTP Ironwax Primer may be required prior to use of LTP Ironwax Satin. For interior use.

**Maintenance:**

Routinely sweep the floor. Use LTP Floorshine to clean and protect the floor. In areas where the seal becomes worn, reseal using more LTP Ironwax Satin. At some stage, complete renovation of the seal may be desired. In this case use LTP Grimex to strip the original seal before re-sealing with LTP Ironwax Satin.

For any technical questions, please ring technical helpline: 01823 666 213.