



**TECHNICAL DATA SHEET
LTP MPG SEALER**

a colourless impregnating sealer for polished marble, porcelain & granite.

A completely natural finish for use on wall & floor surfaces. Easy to apply. May be used indoors or outdoors. May be used on work tops. Strongly protects against water, oil, grease and dirt.

Directions for use:

The surface to be treated must be completely clean, dry and free from contamination e.g. old sealer, dirt and grime. If necessary, first clean floor with LTP Grimex and allow to dry thoroughly. N.B. do not use cement and grout stain removers on polished surfaces. Apply LTP MPG Sealer thinly and uniformly with a cloth, brush or sponge and allow to penetrate for approximately 20 minutes. Buff well with a clean dry cloth and work any excess sealer into the surface. Leave to dry for four hours and apply a second coat using the same method. On more absorbent surfaces, further coats may be applied. It is important to remember to remove any excess on the surface and buff well between each coat. N.B. The aim is to completely fill the substrate with LTP MPG Sealer without over applying it or allowing any excess to oxidise on the surface. Do not apply in temperatures exceeding 25 degrees C. Beware of application upon floors with under floor heating as the product may dry prematurely. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application.

Coverage:

Approximately 10 -20 square metres/litre depending on surface porosity.

Attention:

Storage – Keep cool and dry. Do not use on non-absorbent surfaces. Glass, plastics or any surface which may be adversely affected by this product must be protected against splashes. Removal may be assisted with white spirit on a clean fluff-free rag or wash with LTP Power Stripper.

Health and safety: FLAMMABLE HARMFUL X May cause lung damage if swallowed. Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Keep away from sources of ignition – No Smoking. Keep out of reach of children. Use only in well ventilated areas. Do not breathe vapour. If insufficient ventilation, particularly if spraying, wear suitable respiratory equipment. Avoid contact with eyes and skin. In case of contact with eyes rinse with plenty of water and seek medical advice. If swallowed do not induce vomiting, seek medical advice immediately and show this label/container. In case of fire use foam/dry powder/CO2. Do not use water. After use replace cap firmly and store upright. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings. Please Note -there are no health hazards after the material has dried.

Maintenance:

Keep floor regularly swept or wiped over. Use LTP Waxwash to mop the floor. Use LTP Grimex to remove stubborn surface marks, in which case you may need to re-seal treated areas. N.B. Do not use strong bleach cleaners for routine maintenance. MPG Sealer hardens after about four hours but will take a further three days to achieve full hardness and become fully resistant. It is important not to wet the floor during this three day period.

For any technical questions, please ring technical helpline: 01823 666 213.

Click to see all [stone maintenance products](#)