



TECHNICAL DATA SHEET
LTP COLOUR INTENSIFIER & STAINBLOCK

for enhancing the natural colour in porous quarry tiles, slate, stone & unpolished marble.

Strongly enhances natural colour and appearance of slate, tumbled marble, marble, limestone, granite, other types of natural and artificial stone, terrazzo, quarry tiles etc.,. Provides a matt finish. For use on wall and floor surfaces. May be used indoors or outdoors. May be used on worktops. Strongly protects against water, oil, grease and dirt.

Directions for use:

Important: LTP Colour Intensifier is very difficult to remove once hardened. Therefore, please read instructions carefully. Do not over apply. The surface to be treated must be completely clean, dry and free from contamination e.g. old sealer or polish. If necessary, first clean floor with LTP Grimex and allow to dry thoroughly. Apply LTP Colour Intensifier thinly and uniformly with a cloth, brush, sponge or roller and allow to penetrate for approximately 15-30 minutes before wiping over with a clean dry fluff-free cloth to remove all and any excess which may remain on the surface.

N.B. The surface must retain a matt finish after treatment. Any excess left on the surface will oxidise to form an unsightly gloss varnish. For stronger colour enhancement and in the case of more absorbent surfaces, further coats may be applied. Allow at least 30-60 minutes from application of previous coat before applying further coat.

N.B. The aim is to completely fill the substrate with Colour Intensifier without over applying it or allowing any excess to oxidise on the surface of the tiles. Do not apply in direct sunlight or in a temperature exceeding 25 degrees C. Beware of application upon floors with underfloor heating as the product may dry prematurely. For further enhancement and to provide a shine finish, LTP Clear Beeswax, Ironwax or Ironwax Satin may be applied once the Colour Intensifier has fully cured. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application.

Coverage:

Approximately 3-10 square metres/litre depending on surface porosity.

Attention:

Storage – Keep cool and dry. Do not use on polished, glazed, coated or other non-absorbent surfaces. Glass or polished surfaces, plastics or any surface which may be adversely affected by this product must be protected against splashes. Removal may be assisted with white spirit on a clean fluff-free rag.

Health and safety: FLAMMABLE HARMFUL X May cause lung damage if swallowed. Keep away from sources of ignition – No Smoking. Use only in well ventilated areas. Do not breathe vapour. If insufficient ventilation, particularly if spraying, wear suitable respiratory equipment. Do not breathe vapour. Avoid contact with eyes and skin. Keep out of reach of children. In case of contact with eyes rinse with plenty of water and seek medical advice. If swallowed do not induce vomiting, seek medical advice immediately and show this label/container. Please Note -there are no health hazards after the material has dried.

Maintenance:

Keep floor regularly swept or wiped over. Use LTP Waxwash to mop the floor. Use LTP Grimex to remove stubborn surface marks, in which case you may need to re-seal treated areas.

For any technical questions, please ring technical helpline: 01823 666 213.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

Click to see all [stone maintenance products](#)

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area