

JAN 2008



TECHNICAL DATA SHEET

FRONT:

LTP SPOT STAIN REMOVER

FOR USE ON TRAVERTINE, LIMESTONE, SANDSTONE, SLATE, MARBLE, PORCELAIN, GRANITE, TERRACOTTA, QUARRY TILES, BRICK AND EXTERNAL PAVING.

SUITABLE FOR INTERIOR & EXTERIOR USE

BACK:

LTP Spot Stain Remover

Suitable for Interior & Exterior use

Effective at removing the majority of mineral oil and cooking oil stains (including oil spatters). Suitable for use on travertine, limestone, sandstone, slate, marble, porcelain, granite, terracotta, quarry tiles, brick and external paving.

Combine with LTP Fullers Earth to help remove cooking oil and old stains. The spot stain remover dissolves the stain and the Fullers earth absorbs it by capillary, thus enabling deep down stains to rise to the surface.

Directions for use:

On recent stains:

Apply pure directly onto the stain and leave to react for about 5 minutes.

On cooking oil or old stains:

Apply pure directly onto the stain. Powder the stain with fuller's earth. Wet the powder again with the stain remover and cover it once more with the fuller's earth for the surface to remain dry. Leave to react for 24 hours. Brush away the powder and rinse well with a sponge and water.

Recommendations:

Do not use on wood, rubber, plastic, asphalt, paint or varnish. For stubborn stains renew the application as many times as necessary. After removing the stain, clean the floor with LTP Grimex. Re-seal the floor to protect against further staining.

Coverage:

(Local applications) about 1.5 – 2 sq/m of stains per 500 ml

Attention:

Flammable liquid
Keep out of the reach of children. Do not drink.
Do not breathe the vapour.
Use only in well-ventilated areas. Keep the container in a well-ventilated area. In case of contact with eyes rinse with plenty of water and seek medical advice. In case of swallowing seek medical advice.
Keep away from sources of ignition-No Smoking.



LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN
Tel: +44(0)1823-666-213 www.ltp-online.co.uk Fax: +44(0)1823-665-685

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area